

Environment friendly
and economical boiler
for your home!

Nitromix



DD Demirdöküm

Environment friendly and economical boiler for your home!

Nitromix

108% Efficiency

Nitromix wall hung boilers operate extremely economically with 108% efficiency value. High energy saving provided with high efficiency feature of Nitromix wall hung boiler both protects the consumers and nature.

4-Star Efficiency Class

In 4-star efficiency class according to 92/42/EEC standards imposing high efficiency obligation during minimum and maximum operation.

Stainless Steel Premix Heat Exchanger System

Long lasting stainless steel premix heat exchanger provides high fuel saving and efficiency.

Smart Heating System

Smart heating system provides flame modulation with trafficking NTC sensors according to instant capacity need of the environment. Thus, high efficiency and fuel saving are provided.



Digital Screen and Control Panel

Installation and service water temperature values, water pressure value in installation, and error codes can be monitored thanks to digital screen.

OPF Plus Production Technology

A single operator tracks each wall hung boiler produced along the production line. Close tracking of the products enables raising quality to a maximum level.

MODEL	Nitromix P24	Nitromix P28	Nitromix P35
Technology	Condensing	Condensing	Condensing
Efficiency	108 ««««	108 ««««	109 ««««
Heat Output Max. Kw	23	27	35
Heat Output Max. Kw (DHW)	23	27	35
DHW Heat Output l/min $\Delta T 30^{\circ}C$	11	12.5	15
Fuel Type	NG/LPG	NG/LPG	NG/LPG
Heat Exchanger	Stainless Steel	Stainless Steel	Stainless Steel
Moisture Protection	IPX4D	IPX4D	IPX4D
Power Input	220-240V/50Hz	220-240V/50Hz	220-240V/50Hz
PCB	Self Diagnostic	Self Diagnostic	Self Diagnostic
Control System	Digital	Digital	Digital
Size - Height (mm)	740	740	740
Size - Width (mm)	425	425	425
Size - Depth (mm)	310	340	340
Net Weight (kg)	32.3	34	35.5
Expansion Tank (lt)	7	7	7
Color	White	White	White